Hydraulic Fracturing Conference Offers New Insights

The SPE Hydraulic Fracturing Technology Conference and Exhibition took place 24–26 January in The Woodlands, Texas. The event included more than 50 technical paper presentations, as well as 90 exhibitors, discussing and showcasing new hydraulic fracturing technologies, various applications, and learnings from fracture-stimulated wells. Below are some of the highlights from the conference.

Getting a Better Look at Propped Fractures



• whe Commiss is actions a decome destination

Stephen Rassenfoss, JPT Emerging Technology Senior Editor

C arbo Ceramics is getting a clearer look at where the proppant goes.

The ceramic proppant maker showed much-improved images at this year's conference (SPE 184880) compared with the ones shown last year, as well as a new set of images showing three stages of a Marcellus gas well.

The presentation at the start of the conference's technical sessions drew a large crowd. The method discussed uses metallically coated ceramic proppant that is activated by an electric current run through the reservoir. The new method promises a deep look that is not available using alternatives such as radioactive markers, which are visible only within a couple feet of the wellbore.

A reprocessed image of the first test using the proppant highlighted a challenge: processing the faint signals from proppant grains deep in the ground.

"The key is how do you bring these all together and create a proppant image,"

said Terry Palisch, global engineering director for Carbo, adding that, "the rest is reasonably off-the-shelf technology."

Carbo has spent years developing the sophisticated mathematical formulas required to interpret faint changes in electrical and magnetic signals. In the year since Carbo's paper revealed its work, the company has improved the clarity with more data. It has learned to better locate the receivers on the surface to detect the faint electric and mag-



The image on the left from a well in the Bone Springs formation in west Texas was the first one created using electromagnetic imaging, and the image on the right shows reprocessed data from that 8,000-ft deep lateral revealing far more detail. *Source: Paper SPE 184880.*

Copyright 2017, Society of Petroleum Engineers. Reprinted from the Journal of Petroleum Technology with permission.



The image from a well in the Marcellus shows two small stages on the right side where proppant pumping had to be halted before the planned amount of specially coated ceramic particles (40-70 mesh) was delivered. The large stage at the left received about four times as much proppant after the treatment was altered to ease pumping by lowering the concentration of solids in the fluid, pumping finer-grained proppant (100 mesh) ahead to ease the entry and a linear gel to transport more proppant. *Source: Paper SPE 184880.*

An electromagnetic image of the proppant largely fits into an area, shown in green and turquoise, where a model predicted the most proppant would reside. It also shows significant areas with lower concentrations. *Source: Paper SPE 184880.*



Based on what it learned from its first test, Carbo increased the percentage of receivers picking up electric and magnetic signals. While the two sorts of electromagnetic waves offered similar pictures, adding receivers to pick up magnetic data may offer more volume and detail, perhaps showing areas with lower concentrations of proppant.

"The model suggests there is a threshold of proppant concentration" imaged, Palisch said, adding, "The propped area is larger." The company recently completed the field work for a third test of the system and is now processing that data, he said. It is working to increase the power of the electric current used to stimulate the proppant and use more of the signal and find better ways to reduce noise to create more detailed pictures showing lower proppant concentrations. **JPT**